

SURVEY METHODOLOGIES

The surveys were conducted in accordance with the Minimum Performance Standards for the U.S. Army Corps of Engineers (USACE), Engineering and Design Hydrographic Surveying Manual (EM 1110-2-1003).

This survey is in accordance with Chapter 56.1606 of the North Carolina Administrative Code (NCAC) specifications established by The North Carolina Engineering and Land Surveying Act (GS89C). In addition, all hydrographic surveying was conducted under the direct supervision of an American Congress of Surveying and Mapping (ACSM) Certified Hydrographer (CH). Included in this Topographic and Hydrographic Survey Report are seven (7) maps visualizing profiles, one (1) project location map and six (6) plan view maps. The plan view maps show reduced true position elevation data collected during the survey. The location of all published control, as well as control found and used for survey purposes, is presented in the Monument Information Report provided in **Appendix 1**.

Vertical data was collected in the North American Vertical Datum of 1988 (NAVD88). All Horizontal data is provided in the North Carolina State Plane Coordinate System, North American Datum of 1983(2011) (NAD 83(2011)). Profile data is presented in xyz format relative to The North American Vertical Datum of 1988 (NAVD88) in **Appendix 2** (digital format only). Profile plots are provided in **Appendix 3**. Ground digital photography obtained during the survey is provided in **Appendix 4**. Copies of all field book pages are provided in **Appendix 5** (digital format only).

The field survey and data collection activities encompassed four (4) phases. Brief descriptions of each survey phase, including methodologies and quality control/quality assurance procedures, are described below.

Phase One: Control Reconnaissance/Establishment/Verification

Prior to the start of the survey, reconnaissance of the monuments was conducted to confirm that survey control was in place and undisturbed. Real Time Kinematic Global Positioning System (RTK GPS) was used within a virtual reference station (VRS) network to locate and confirm survey control for this project. The North Carolina Geodetic Survey Continuously Operating Reference Station (CORS) Network stations used for this project included NCDU (Duck 3), NCBI (Bodie Island), NCBX (Buxton), NCEL (Elizabeth), and NCCR (Creswell). The horizontal and vertical accuracy of control data meets the accuracy requirements as set forth in the Engineering and Design Hydrographic Surveying Manual (EM 1110-2-1003). In order to achieve required accuracy, the topographic and hydrographic surveys were controlled using 2nd order monuments, specifically WAY, KITTY, CAFFEY, X254, and

Y254 from the National Geodetic Survey (NGS). Horizontal and vertical positioning checks were conducted at the beginning and end of each day using at least two 2nd order monuments in the project area. The RTK GPS utilizes statistical methods to ensure accuracy of RTK GPS data remains within the 95% confidence interval. The control check shots were acquired using a minimum of five (5) epochs which results in a high accuracy location. Results from 2nd order control checks are displayed showing northing, easting, monument elevation, inverses, horizontal and vertical root mean square error, location description and photographs as indicated in the Monument Information Report (**Appendix 1**).

Phase Two: Beach Profiles

Upon completion of the control reconnaissance survey, beach/upland and nearshore operations were initiated. Cross-sections of the beach in the project area were surveyed using extended rod RTK GPS rovers, and standard RTK GPS rovers. Extended rod RTK GPS rovers were used to augment RTK GPS survey capability into the nearshore. The current systems allow surveyors from APTIM to collect the entire beach profile with RTK GPS technology. Incorporation of RTK GPS into monitoring surveys greatly reduces the potential for human error during data collection and reduction.

Profiles commenced from the onshore control point and extend seaward overlapping the offshore data. Nearshore portions of the profiles were surveyed by two (2) surveyors with an Extended Rod Trimble R8 and R10 RTK GPS rovers who entered the water wearing Personal Floatation Devices (PFD). Trimble TSC3 data collectors are equipped with Bluetooth technology allowing wireless communication with the GPS receiver at a data exchange speed of 2.1 megabits per second. The rover system allows surveyors from APTIM to reach a maximum water depth of eleven (11) feet. The nearshore survey extended seaward to a point overlapping the offshore portion of the profiles by at least fifty (50) feet.

The upland portion of the survey commenced at the waterline and extended 250 feet landward of the dune or until an obstacle was encountered. The upland portions of the profiles were surveyed using an RTK GPS. Elevations were taken at approximately twenty-five (25) foot intervals along each profile line and at all grade breaks. To maintain online accuracy, surveyors utilized the RTK GPS feature *stakeout point*. *Stakeout point* allows surveyors to maintain the profile azimuth without relying on a survey lathe or conventional compass bearings.

Phase Three: Nearshore/Offshore Profiles

The Nearshore/Offshore profiles were conducted at each required profile station. The profiles were obtained 2,500 feet beyond the shoreline or to the -30 NAVD88 contour, whichever is more landward. The landward limits of the nearshore profiles were based on a minimum overlap of fifty (50) feet beyond the seaward extent of beach profiles. Soundings were

collected at 200kHz with an Odom Hydrotrac II single frequency sounder connected to a centrally located, hull-mounted transducer on APTIM's twenty-eight (28) foot Parker survey vessel. These soundings were then reduced to 25' spacing, sufficient to provide an accurate depiction of the seafloor.

Data was digitally stored using HYPACK 2020 Software. A Trimble R8 RTK GPS and a TSS DMS-25 dynamic motion sensor were used onboard the survey vessel to provide instantaneous tide corrections and attitude corrections. Manual tide readings were taken while conducting the onshore portion of the profile to verify onboard tide readings. In order to maintain the vessel navigation along the profile lines, HYPACK 2020 navigation software was used. This software provided horizontal position to the sounding data allowing real-time review of the data in plan view or cross-section format. HYPACK 2020 also provided navigation to the helm to minimize deviation from the online azimuth.

Horizontal and vertical positioning checks were conducted at the beginning and end of each day as described in phase one (1) of the survey. The sounder was calibrated via bar-checks and a sound velocity probe at the beginning and end of the day. The DIGIBAR PRO sound velocity meter offers a fast, additional calibration for sound velocity as compared to the traditional bar-check. Bar-checks were performed from a depth of five (5) feet to a depth of at least twenty-five (25) feet. Analog data showing the results of the bar-check calibration was displayed on the sounder charts at five (5) foot increments during descent of the bar. Offshore data was collected within two (2) weeks of onshore data collection for each line.

Phase Four: Data Reduction/Submittals

Upon completion of the field work, data was edited and reduced with Trimble Business Center, HYPACK 2020, and APTIM's internal software programs. The upland and nearshore portions of the beach profile were viewed and edited in Trimble Business Center and a comma delimited XYZ file was created. The offshore raw digital data was viewed and edited in HYPACK 2020's *Single Beam Editor*. The offshore RTK GPS tide data that was collected was compared to the manually collected RTK GPS nearshore tide data, local observed, and predicted tides for data verification purposes. Tide corrected offshore data was exported and a comma delimited XYZ file was created. All overlapping profile data was compared in cross section to ensure system accuracy. The edited beach profile data and offshore profile data were merged, and a representative cross-section was derived for each profile line. The cross sections were developed using internal APTIM plotting programs.

The final plots were edited and reviewed with comparisons to previous years; discrepancies were noted and resolved. The final approved cross-section data was prepared in the required formats for submittal (**Appendix 3**). Digital data is provided in the State required vertical datum NAVD88.

Map Preparation:

Upon completion of the surveys and data reduction, the survey maps were prepared in ArcGIS 10.7.1. In order to avoid congestion, the survey maps do not show all collected elevations, but enough to give an accurate depiction of the cross sections. The survey maps display profile data and control monument locations plotted against Esri's background aerial imagery from March, 2018.

Ground Digital Photography:

Surveyors from APTIM collected three (3) digital photos at a mid-beach location at each profile location. The three (3) photos included one (1) in each shore-parallel direction and one (1) landward toward the monument. Wherever possible, an additional digital photo was taken of the control identification or stamping on the monument.